



POWRi Safety Requirements

Index

Uniforms.....	3
Gloves.....	3
Socks.....	3
Shoes.....	3
Arm Restraints.....	3
Helmets.....	3
Head & Neck Restraints.....	3
Headrests.....	4
Seats.....	4
Seat Belts.....	4
Roll Cage Padding.....	4
Steering Wheel Padding.....	4
RACEceiver Radios.....	4
Fire Equipment.....	4
Ending Statement.....	5

Uniforms

- a. All Drivers must wear an approved one-piece racing uniform. Fire retardant head sock and/or skirt, socks, gloves, underwear, and shoes are highly recommended.
- b. A driver suit certified to SFI Spec 3.2A/5 is required to be always worn during competition or on the racing surface.

Gloves

- a. Gloves certified to SFI Spec 3.3 are required to be always worn during competition or on the racing surface.

Socks

- a. Socks certified to SFI Spec 3.3 are required to be always worn during competition or on the racing surface.

Shoes

- a. Shoes certified to SFI Spec 3.3 are required to be always worn during competition or on the racing surface.

Arm Restraints

- a. Arm restraints are not mandatory but highly recommended to be worn at all times during competition.

Helmets

- a. All drivers must wear a full-face helmet.
- b. A helmet certified to Snell SA2015/FIA-8859-2015, Snell SA2020/FIA-8860-2018, SFI 31.1/2015 or SFI 31.1/2020 is required to be always worn during competition or on the racing surface.

Head & Neck Restraints

- a. At all times during an event, drivers must connect their helmet to a head and neck restrain device system certified to SFI Spec 38.1.
- b. The head and neck restraint system, when connected, must conform to the manufacturer's mounting instructions, and must be configured, maintained, and used in accordance with the manufacturer's instructions

Headrests

- a. It is mandatory that all cars have a headrest of high impact, shock-absorbing material meeting SFI Specification 45.2 behind the driver's head with a minimum thickness of one (1) inch.

Seats

- a. Approved full containment seats are required.
- b. Approved aluminum and composite seats may be used, no fiberglass.
- c. Seats must be mounted with a minimum of four (4) bolts 5/16 diameter.
- d. Seats must be installed in accordance with manufacturer's instructions.

Seat Belts

- a. Seat belts must be five points and properly attached and/or supported.
- b. Seat belts must meet SFI 16.5 or SFI 16.1, be within manufacturer's expiration label (must have label). Seat belts must be installed and used in accordance with manufacturer's instructions.
 - i. No Y seatbelt mounts will be allowed.
 - ii. No low back seats allowed.
 - iii. No more than two (2) years old.

Roll Cage Padding

- a. All chassis protrusions, roll cage tubes and roll bars near the driver's helmet are highly recommended to be padded with a securely attached high impact material conforming to SFI Specification 45.1. This includes any vertical anti-intrusion supports alongside the driver.

Steering Wheel Padding

- a. The steering wheel hubs are highly recommended to be padded with resilient material of not less than $\frac{3}{4}$ " thickness.

RACEceiver Radios

- a. Driver Radios are mandatory every time a competitor hits the race track.
- b. A POWRi Official/Race Director/Division Official reserves the right to penalize and fine drivers that do not run a RACEceiver.
- c. No radio communication to drivers except from club or track officials.

Fire Equipment

- a. The Entrant or Crew Chief of each car should have in his pit a fully charged five-pound powder fire extinguisher, or its equivalent. A gauge or current inspection should be attached to each fire extinguisher.

- b. Fire Suppression system is HIGHLY recommended and WILL be mandated in the future.

Ending Statement

- a. All race cars and driver's equipment are subject to safety inspections. The Series and/or Safety Director reserves the right to refuse a car or driver from competition, if deemed unsafe.